



PERFORMANCE SPORTS SYSTEMS

MODEL 1750B

35-1/2" X 53 1/2" FAN SHAPED ALUMINUM BACKBOARD WITH WHITE POWDER COATED FINISH AND ORANGE BORDER AND TARGET

The 1750B backboard shall be a one-piece permanent mold, aluminum alloy casting with a 1-1/4" flange around outer edge. Backboard shall have eight mounting holes, which shall be reinforced with cast in-place threaded steel inserts for 3/8-16 bolts. 1/4" wide and 1" deep ribs reinforce the board mounting inserts and the goal mounting holes.

Backboard shall have a 5" horizontal and a slotted vertical goal mounting holes to accommodate hole patterns from 5" vertical to 4.25 vertical.

FINISH

Backboard surface shall have a white powder coated finish with an orange border and target silk-screened on face for permanent markings.

ACCESSORIES

GOALS

See Goal-Board Matrix specification sheet for goal compatibility.

NOTICE

PROPER TIGHTENING OF FASTENERS IS IMPORTANT TO ASSURE ALL COMPONENTS HAVE BEEN INSTALLED AND SECURED CORRECTLY. THE FOLLOWING TABLE LISTS THE RECOMMENDED TIGHTENING TORQUE FOR BOLTS USED IN THE INSTALLATION. DURING THE INSTALLATION TIGHTEN ALL BOLTS TO THE RECOMMENDED TIGHTENING TORQUE LISTED IN THE TABLE UNLESS OTHERWISE SPECIFIED IN THE ASSEMBLY INSTRUCTIONS.

RECOMMENDED BOLT TORQUE			
BOLT SIZE	WRENCH SIZE	Inch-Pounds	Foot-Pounds
1/4	7/16	66 to 90	5.5 to 7.5
5/16	1/2	132 to 180	11 to 15
3/8	9/16	234 to 318	19.5 to 26.5
7/16	11/16		31 to 42.5
1/2	3/4		47 to 65
9/16	7/8		68 to 90
5/8	15/16		94 to 130
3/4	1 1/8		166 to 230
7/8	1 5/16		269 to 372
1	1 1/2		402 to 566