



- 
- Diagram illustrating the post and footing assembly for the 10' x 10' x 10' ft. post. The diagram shows a cross-section of the post and footing, with dimensions and labels indicating the components and measurements.
- Labels:** CAR, POST LOCATIONS, EYEBOLTS, MEASURED INSIDE TO INSIDE 22'-0" APART, 11'-0", COLLAR, TAKE UP POST, DUMMY POST, GROUND SLEEVE (RECOMMENDED), CENTER ANCHOR (PURCHASED SEPARATELY).
  - Dimensions:**
    - Post diameter: 10'-0"
    - Post length: 10'-0"
    - Post locations: 22'-0" apart (measured inside to inside).
    - Post spacing: 11'-0" (between posts).
    - Post collar: 18" (width).
    - Post take up post: 24" (width).
    - Post dummy post: 36" (width).
    - Post center anchor: 12" (width).
    - Post footing dimensions: 24" (width), 30" (width).
    - Post footing height: 3'-0" (height).
    - Post footing depth: 9" (depth).
    - Post footing width: 12" (width).
  - Notes:** THE FOOTING DIMENSIONS ILLUSTRATED ARE APPROXIMATE AND MAY BE VARIED IN DIFFERENT REGIONS ACCORDING TO LOCAL SOIL AND FROST CONDITIONS.

WHITE CORD, TIE OFF AT EYE BOLT

CABLE

DOWEL

HEADBAND

TOP EYEBOLT

CABLE HOOK

SIDE TAP

GROMMET

BOTTOM BAND

34"

CENTER STRAP (PURCHASED SEPARATELY FROM NET)

BLACK CORD

TURN CLOCKWISE TO TIGHTEN

TO RELEASE TENSION PIVOT THE SIDE GEAR COVER

BOTTOM EYEBOLT

DUMMY POST

CENTER STRAP

TAKE UP POST

MOUTH MOVABLE HANDLE

NET INSTALLATION

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.CADdetails.com/info](http://www.CADdetails.com/info) AND ENTER REFERENCE NUMBER 2763-061.

